



THE COMPANY

SHREE PAWAN MULTINATIONAL PVT LTD. has come long way since its small beginning in the 2012. It was set as a firm by the dynamic personality Mr. PAWAN KUMAR who was willing to take on the most trusted, famous and biggest Indian Brand. Over the course of 5 years PORT GUARD became a corporate force and India's most established brand. Today it is triple the size of what it was at its inception.

MD's DESK

It takes a lot of passion, determination and patience to transform ideas into effective solutions and even more to turn those into products which contribute to success. It is this passion that has made PORT GUARD one of the best white cement based wall coats and allied products in India. Our aim was to strike a balance between price and services. Prices those were affordable to the end users without compromising on the quality and services that gave complete solution with much research and experiment.

We decided to manufacture to wall coats and premixed products and thus PORT GUARD was formed in July 2009. In a short span of time, PORT GUARD wall putty and other products captured vast market with its superior quality products and affordability. Now the consumers have yet another and better option to go for professional plastering solutions.

Since PORT GUARD has become a brand to reckon with, to be recognized with and to be associated with our dream of creating the most trusted Indian company worldwide by creating value to all thus growing phenomenally has been realized. We have also started focusing on capturing and conquering global markets. With this we aim and strive to take PORT GUARD to greater heights and achievements in all markets and maintaining continuous interaction with consumers to understand their emerging requirement so as to be ready when the need arises.



PORT GUARD[®] PURE X EXTERIOR EMULSION

Port Guard Purex Exterior Emulsion is a premium quality exterior emulsion with the state of art technology having smooth and uniform finish which is used to give the excellent and beautiful colours to your exterior walls.

METHOD OF APPLICATION

- 01 SURFACE PREPARATION:** First of all prepare a surface free from all waterproofing issues. Surface must be free from dirt, dust, algae/fungi & loose flaking paint etc.
- 02 PUTTY (If Required):** Apply a thin coat of Wall Putty to fill any dents/minor hairline cracks or to smoothen the surface. Allow it to dry for 6-8 hrs.
- 03 PRIMING:** Apply a coat of "Port Guard Wall Primer" by thinning with potable water and allow it to dry for 4-6 hrs.
- 04 APPLICATION:** Apply 2-3 coats of "Port Guard PureX Exterior Emulsion" by thinning with potable water 40% by volume. Maintain a gap of 4-6 hrs between coats. Avoid excess dilution for better performance.



PURE BRIGHT FINISH



EXCELLENT HIDING CAPACITY



SUPER SMOOTH FLOW



HIGH COVERAGE

01 Ltr. 04 Ltr. 10 Ltr. 20 Ltr. PACK SIZE

Colour Variants available with extra cost.

PORT GUARD[®] D'CENT INTERIOR EMULSION

Port Gurd D'cent Interior Emulsion is made with the high class technology that gives you superior features and a wide array of color choice.

METHOD OF APPLICATION

- 01 **SURFACE PREPARATION:** First of all prepare a surface free from all waterproofing issues. Surface must be free from dirt, dust, algae/fungi & loose flaking paint etc.
- 02 **PUTTY (If Required):** Apply a thin coat of Port Guard Wall Putty to fill any dents/minor hairline cracks or to smoothen the surface. Allow it to dry for 6-8 hrs.
- 03 **PRIMING:** Apply a coat of "Port Guard Interior Wall Primer" by thinning with potable water and allow it to dry for 4-6 hrs.
- 04 **APPLICATION:** Apply 2-3 coats of "Port Guard D'Cent Interior Emulsion" by thinning with potable water 40% by volume. Maintain a gap of 4-6 hrs between coats. Avoid excess dilution for better performance.



PORT GUARD[®] WALL PUTTY (WHITE CEMENT & POLYMER BASED)

Port Guard Wall Putty is a water resistant white cement and polymer based putty which provides a strong base on concrete (internal and external) and ceiling. It is applied before painting of the wall. It fills the fine pores of the walls and ceiling thereby providing a white smooth and dry surface for painting. Being water resistant it provides a protective base which prevents expensive paints from falling.

Port Guard White Cement Wall Putty has special added polymers provides a strong base ensuring a longer life for the painted surface.



**FUNGUS
RESISTANCE**



**FAST
DRYING
SKILL**



**EXCELLENT
HIDING
CAPACITY**



**HIGH
COVERAGE**

PACK SIZE 01 Ltr. 04 Ltr. 10 Ltr. 20 Ltr.

Colour Variants available with extra cost.



**EXCELLENT
COVERAGE**



**MATT
FINISH**



**SUPERIOR
SMOOTH
QUALITY**

05 Kg. 20 Kg. 40 Kg. PACK SIZE



PORT GUARD[®] DECORATIVE WHITE CEMENT

Port Guard is one of the best "Whitest White Cement" It helps in developing a pristine white canvas for crafting architectural elegance. It's the key ingredient in the application of decorative cement paints, mosaic tiles, terrazzo floorings and marble laying. Its remarkably high refractive index and high opacity imparts a gleaming luster and smooth finish to surfaces.

Besides, it's also a significant constituent in wall finishes such as Grit Wash, Stonecrete and Tyrolean.



**EXCELLENT
ADHESION**



**QUICK DRYING
CAPACITY**



**MULTI PURPOSE
USE**

PACK SIZE 01 Kg. 05 Kg. 25 Kg. 50 Kg.



PORT GUARD[®] CYCLONE LUXURY EMULSION

Port Guard Cyclone Luxury emulsion is an exquisite emulsion paint that provides luxurious finish and a glowing appearance to your walls. Its anti fungal technology make it highly resistant to fungal growth on your walls and gives smooth finish to your walls everytime. Its free from lead contents and gives high coverage and low in VOC.

METHOD OF APPLICATION

- 01 SURFACE PREPARATION:** First of all prepare a surface free from all waterproofing issues. Surface must be free from dirt, dust, algae/fungi & loose flaking paint etc.
- 02 PUTTY (If Required):** Apply a thin coat of Port Guard Wall Putty to fill any dents/minor hairline cracks or to smoothen the surface. Allow it to dry for 6-8 hrs.
- 03 PRIMING:** Apply a coat of "Port Guard Wall Primer" by thinning with potable water and allow it to dry for 4-6 hrs.
- 04 APPLICATION:** Apply 2-3 coats of "Port Guard Cyclone Luxury Emulsion" by thinning with potable water 40% by volume. Maintain a gap of 4-6 hrs between coats. Avoid excess dilution for better performance.



**FUNGUS
RESISTANT**



**FAST DRYING
CAPACITY**



**HIGH
COVERAGE**



**PEELING, CRACK
& FADING
RESISTANT**

01 Ltr. 04 Ltr. 10 Ltr. 20 Ltr. PACK SIZE

Colour Variants available with extra cost.

PORT GUARD[®] WALL SMITH

INTERIOR PRIMER

Port Guard Wall Smith Interior Primer is a water base interior primer which gives a protective undercoat with alkali resistant property. It is suitable for interior plastered, masonry, POP or pre painted surfaces. It is specially formulated to give excellent adhesion to all interiors.

METHOD OF APPLICATION

- 01 **SURFACE PREPARATION:** First of all prepare a smooth and uniform surface. This can be done by scraping the old painted surface and removing the flanking particles and all the dirt or dust which is present on the surface.
- 02 **MIXING:** Stir and strain the material before using it. Now thin the primer with 25% to 30% of clean water by volume, but don't over-thin. Apply at least 2-3 coats for smooth finish with Brush or Roller.
- 03 **APPLICATION:** A brush, roller can be used to apply Port Guard WallSmith Interior Primer". The equipment should be washed after use.
- 04 **RECOATING:** Let the coat dry, Leave for 2 to 4 hour, then apply another coat.



GREATER
COVERAGE



EXCELLENT
HIDING
CAPACITY



SUPER
QUICK
DRYING



MATT
FINISH

PACK SIZE 01 Ltr. 04 Ltr. 10 Ltr. 20 Ltr.



PORT GUARD[®] SPOT LIGHT

EXTERIOR WALL PRIMER

Port Guard Spot Light Exterior Wall Primer is a water base exterior wall primer its undercoat suitable for exterior surfaces. Formulated with special pigment to ensure longer life to the entire painting system. This primer seeps through the permeable surfaces and seals it. Moreover this primer provides exceptional whiteness and opacity.

METHOD OF APPLICATION

- 01 **SURFACE PREPARATION:** First of all prepare a smooth and uniform surface. This can be done by scraping the old painted surface and removing the flanking particles and all the dirt or dust which is present on the surface.
- 02 **MIXING:** Stir and strain the material before using it. Now thin the primer with 25% to 30% of clean water by volume, but don't over-thin. Apply at least 2-3 coats for smooth finish with Brush or Roller.
- 03 **APPLICATION:** A brush, roller can be used to apply Port Guard SpotLight Exterior Wall Primer". The equipment should be washed after use.
- 04 **RECOATING:** Let the coat dry, Leave for 2 to 4 hour, then apply another coat.



EXCELLENT
COVERAGE



EXCELLENT
HIDING
CAPACITY



SUPER
QUICK
DRYING



MATT
FINISH

01 Ltr. 04 Ltr. 10 Ltr. 20 Ltr. PACK SIZE

PORT GUARD[®] GLAZE SMITH

UNIVERSAL PRIMER

Port Guard Glaze Smith Universal Primer provides the excellent features like superior filling property, Alkaline resistant and good adhesion. It makes walls protected against fungi, Algae, dampness caused by lashing rain water.

METHOD OF APPLICATION

- 01 **SURFACE PREPARATION:** First of all prepare a smooth and uniform surface. This can be done by scraping the old painted surface and removing the flanking particles and all the dirt or dust which is present on the surface.
- 02 **MIXING:** Stir and strain the material before using it. Now thin the primer with 25% to 30% of clean water by volume, but don't over-thin. Apply at least 2-3 coats for smooth finish with Brush or Roller.
- 03 **APPLICATION:** A brush, roller can be used to apply Port Guard GlazeSmith Universal Primer". The equipment should be washed after use.
- 04 **RECOATING:** Let the coat dry, Leave for 2 to 4 hour, then apply another coat.



ALKALINE
RESISTANT



EXCELLENT
HIDING
CAPACITY



QUICK DRYING
WITH GRATER
COVERAGE



MATT
FINISH

PACK SIZE 01 Ltr. 04 Ltr. 10 Ltr. 20 Ltr.



PORT GUARD[®] COLOR SMITH

ACRYLIC DISTEMPER

Port Guard Color Smith Acrylic Distemper is a water based interior wall paint. It is the best quality acrylic distemper which gives the walls a smooth and delightful matt finish that lasts for ages. A tested formulation of acrylic co-polymers binders used to give unmatched performance It also comes in a wide range of attractive shades.

METHOD OF APPLICATION

- 01 **SURFACE PREPARATION:** First of all prepare a smooth and uniform surface. This can be done by scraping the old painted surface and removing the flanking particles and all the dirt or dust which is present on the surface.
- 02 **PUTTY:** Make the surface smooth by applying minimum two coats of "Port Guard Wall Putty" allow the surface to dry for 6 -8 hours. Rub the surface with emery paper 180 no. To further smoothen the surface.
- 03 **APPLICATION:** Apply one coat of "Water Thinnable Cement Primer". Take 1 Kg. of "Port Guard ColorSmith Acrylic Distemper" and Add 500 -600 ml. of water to make it thin for brushability and apply the first coat. Apply the second coat after an interval of 6-8 hours.



EXCELLENT
COVERAGE



MATT
FINISH



SUPERIOR
SMOOTH QUALITY



FANTASTIC
SHADE RANGE

01 Kg. 02 Kg. 05 Kg. 10 Kg. 20 Kg. PACK SIZE

Colour Variants available with extra cost.